

Datasheet

Industrial PVC-cables H03VVH2-F

Technical attributes

Standards	DIN VDE 0281- 5
Conductor material	Cu, bare
Conductor type	Cu-bare
Conductor category	5
Conductor standard	DIN VDE 0295
Core colours	DIN VDE 0293
Outer sheath	PVC
Outer sheath colour	black, white or on request
Temperature range min., mobile operation	+5 °C
Temperature range max., mobile operation	+70 °C
Temperature range min., fixed installation	-40 °C
Temperature range max., fixed installation	+70 °C
Nominal voltage Uo/U	300/300 V
RoHS-compliant	yes



Description

For use on lightweight hand-held devices with low mechanical stress as well as for connecting light electrical appliances such as kitchen appliances, office equipments and radios. Not suitable for cooking and heating appliances and also not suitable for outdoor use in industrial and agricultural businesses and to connect power tools used.

Note

PVC multi core cable

Product table

product number	product name	Weight ca. [kg]	Cu-weight [kg_km]	Outer-Ø ca. [mm]	Outer sheath colour
13280	H03VVH2-F 2 x 0,75 bk RAL 9000	32,00	14,40	5,60	RAL 9005 black
	H03VVH2-F 2 x 0,75 gold	32,00	14,40	5,60	gold
13279	H03VVH2-F 2 x 0,75 wh RAL 9010	32,00	14,40	5,60	RAL 9010 white
	H03VVH2-F 2 x 0,75 bn RAL 8014	32,00	14,40	5,60	brown
15425	H03VVH2-F 2 x 0,75 gy RAL 7035	32,00	14,40	5,60	grey
13410	H03VVH2-F 2 x 0,75 gy RAL 7000	32,00	14,40	5,60	RAL 7000 gray