

Datasheet

SPEAKERCABLE Eca

Acc. to EN 50575:2014

GRADE A, 99,9% pure Oxygen Free Copper

STANDARD	2 x 0,75 mm ²	2 x 1,50mm ²	2 x 2,50mm ²
Core	24 x 0,20 mm	48 x 0,20 mm	78 x 0,20 mm
Isolation	PVC, Black with red stripe or Transparant with red stripe	PVC, Black with red stripe or Transparant with red stripe	PVC, Black with red stripe or Transparant with red stripe
Dimensions (+/- 0,15 mm)	2,2 mm x 4,8 mm	2,6 mm x 5,8 mm	3,60 mm x 7,5 mm
Wall thickness (+/- 0,10 mm)	0,57 mm	0,63 mm	0,58 mm
Weight	23,0	37,0	62,0
Copper	14,4	30,0	50
Conductor Res. Ohm/km	22.00 per conductor	11,00 per conductor	6,83 per conductor

STANDARD	2 x 4,00 mm ²	2 x 6,00mm ²
Core	126 x 0,20 mm	189 x 0,20 mm
Isolation	PVC Transparant with red stripe	PVC, Transparant with red stripe
Dimensions (+/- 0,15 mm)	4,4 mm x 9,5 mm	5,2 mm x 10,8 mm
Wall thickness (+/- 0,10 mm)	0,90 mm	0,90 mm
Weight	105	141
Copper	80	120
Conductor Res. Ohm/km	4,20 per conductor	3,30 per conductor

-Made in Germany-

