



(product image is just as an indication)

Technical specifications

Conductor 1	CuAg 0,90mm
Conductor 1 (resistance)	28 Ohm/Km
Dielectric	PE 2,95 mm
Braid 1	CuAg 95 %
Braid 2	CuAg 90 %
External Jacket	PVC Black
External Jacket (diameter)	5,4 mm
Impedance	50 ± 2 Ohm
Mutual/coax capacity	97 ± 2 pF/m
Velocity Ratio	66 %
Screening Efficiency (30-1000 MHz)	> 70 dB
Temperature rating	-20/+85 °C
Screen Resistance	4,5 Ohm/Km
Test Voltage	2 KVac
Minimun bending radius	8 x O.D.
Weight	5,3 Kg/100m

Part Num.

RG223NE

Description

RG 223 M-17/84

Family

50 OHM RG CABLES

Electrical Features

Freq.	Atten. dBx100m	RL dB
50	10,5	100-300MHz > 35
230	23,6	300-900MHz > 30
470	33,8	
860	43,9	
1000	54,2	

More info...

Packaging

M100
B500
B1000

Standards

MIL C-17

Applications

Distribution of radio frequency signals and transceivers.

Markings

Date, ITC, part number, Mil C 17 F, meters



REV.22/11/2016 09:43:09

ITC S.R.L.
Via Bora, 4
48012 Bagnacavallo
Ravenna - Italy

Tel. 0545 60470
www.itc-belden.com