



## Product: [9534](#)

RS-232, #24-4c, SR-PVC, O/A Foil, PVC Jkt, CMG

### Product Description

Computer EIA RS-232 Cable, 24 AWG stranded (7x32) tinned copper conductors, PVC insulation, overall Beldfoil® shield (100% coverage), 24 AWG stranded tinned copper drain wire, PVC jacket.

### Technical Specifications

#### Physical Characteristics (Overall)

##### Conductor

AWG	Stranding	Material	No. of Conductors
24	7x32	TC - Tinned Copper	4

Conductor Count: 4

##### Insulation

Material	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.01 in

##### Color Chart

Number	Color
1	Black
2	White
3	Red
4	Green

##### Outer Shield Material

Material	Material Trade Name	Coverage (%)	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Alum / Poly	Beldfoil®	100 %	TC - Tinned Copper	24	7x32

##### Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.184 in	0.032 in

#### Electrical Characteristics

##### Conductor DCR

Nominal Conductor DCR	Nominal Outer Shield DCR
25 Ohm/1000ft	18 Ohm/1000ft

##### Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
33 pF/ft	65 pF/ft

##### Current

Max. Recommended Current [A]
1.75 Amps per conductor @ 25°C A

##### Voltage

**UL Voltage Rating**

300 V RMS

**Temperature Range**

UL Temp Rating:	80°C (UL AWM Style 2464)
Operating Temp Range:	-30°C To +80°C

**Mechanical Characteristics**

Bulk Cable Weight:	20 lbs/1000ft
Max Recommended Pulling Tension:	22 lbs
Min Bend Radius/Minor Axis:	2 in

**Standards**

NEC/(UL) Specification:	CMG
CEC/C(UL) Specification:	CMG
UL AWM Style:	2464 (300 V 80°C)
CPR Euroclass:	Eca

**Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
MII Order #39 (China RoHS):	Yes

**Flammability, LS0H, Toxicity Testing**

UL Flammability:	UL1685 FT4 Loading
CSA Flammability:	FT4
ISO/IEC Flammability:	IEC 60332-1-2
UL voltage rating:	300 V RMS

**Plenum/Non-Plenum**

Plenum (Y/N):	No
---------------	----

**Part Number****Variants**

Item #	Color	Putup Type	Length	UPC/EAN
9534 060Z1000				612825427476
9534.0030	Chrome	Reel	30 m	8719605021731
9534.00U152	Chrome	UnReel	152 m	8719605021748
9534.00U305	Chrome	UnReel	305 m	8719605021755
9534.01152	Chrome	Reel	152 m	8719605021762
9534.01305	Chrome	Reel	305 m	8719605021779
9534 060U1000	Chrome	UnReel	1,000 ft	612825255086
9534 060U500	Chrome	UnReel	500 ft	612825255093
9534 060100	Chrome	Reel	100 ft	612825255109
9534 0601000	Chrome	Reel	1,000 ft	612825255116
9534 060500	Chrome	Reel	500 ft	612825255123
9534 0605000	Chrome	Reel	5,000 ft	612825255130

Footnote:

C - CRATE REEL PUT-UP.

**History**

Update and Revision:

Revision Number: 0.307 Revision Date: 04-08-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.