



**Product:** [70048LV](#)

**SPEAKERCABLE LSZH 2x4.0mm<sup>2</sup>**

**Product Description**

SPEAKERCABLE LSZH 2x4.0mm<sup>2</sup>

**Technical Specifications**

**Product Overview**

Environmental Space:	Indoor/Outdoor - Euroclass B2ca
Suitable Applications:	Speaker cable for use in indoor or outdoor applications

**Physical Characteristics (Overall)**

**Conductor**

Stranding	Material	Cross Section	Construction n x D
Stranded	BOFC - Bare Oxygen free Copper	4.00 mm <sup>2</sup>	56x0.30 mm

Conductor Count:	2
------------------	---

**Insulation**

Type	Material	Nominal Diameter	Diameter +/- Tolerance
Insulation	FRNC / LSZH	3.30 mm	0.1 mm

**Color Chart**

Number	Color
Wire 1	Black
Wire 2	Red

**Outer Jacket Material**

Material	Nominal Diameter	Diameter +/- Tolerance
LSZH / FRNC with matte finish	8.60 mm	0.25 mm

**Construction and Dimensions**

**Cabling**

Description
2 wires twisted

**Electrical Characteristics**

**Conductor DCR**

Max. Conductor DCR
4.5 Ohm/km

**Voltage**

Voltage Rating [V]
300 V

**Temperature Range**

Storage Temp Range:	-30°C to +70°C
---------------------	----------------

Operating Temp Range (Flexible Install):	-5°C To +60°C
Operating Temp Range (Fixed Install):	-30°C To +70°C

## Mechanical Characteristics

Max Recommended Pulling Tension:	550 N
----------------------------------	-------

## Standards

CPR Euroclass:	B2ca-s1,d,1,a1
----------------	----------------

## Flammability, LSOH, Toxicity Testing

ISO/IEC Flammability:	IEC 60332-1-2
Amount of Halogen acc. to IEC 60754-1 & EN50267-1:	Zero

## Part Number

### Variants

Item #	Color	Length
70048LV.00500	Black	500 m
70048LV.009999	Black	499 m

## History

Update and Revision:	Revision Number: 0.16 Revision Date: 01-31-2020
----------------------	-------------------------------------------------

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.