

03.09.2026

Announcement of Product Change notification – Enhanced Outdoor Rating for IEC-EN LSZH Cables

Dear Valued Customer,

We are pleased to announce an enhancement to our IEC-EN LSZH cable portfolio. Effective March 9, 2026, these products will be officially rated for general outdoor use, providing greater flexibility for transitions between indoor and light outdoor applications.

This enhancement is a result of our continuous material testing and deep expertise in cable performance. The cable's form, fit and function remain unchanged, ensuring the same high-quality product you expect from Belden.

As part of this update, we are also providing more specific details on sunlight resistance. However, it is important to clarify that these cables are designed for light, general outdoor use only. **They are not suitable for heavy-duty outdoor applications, such as direct burial or in environments with long-term water exposure or high mechanical stress.** For more detailed information, please refer to our technical bulletin: [General Outdoor Suitability for Wire and Cable](#).

Key dates:

Milestone	Date
Announcement Date	2026-03-09
Expected date of change	2026-03-09

Thank you very much for your trust in our company and if you have any questions or remarks, please contact your local Belden sales representative.

Sincerely,
Belden Wire & Cable Solutions

i.V. Yorick Carisey
Product Line Manager

i.V. Noel Aben
Product Line Manager

i.V. Theo van Rijn
Product Line Manager

Product Family	Short Description	Previous Environmental Suitability	New Environmental Suitability (March 2026)
1502ELW	Media Control, #18-2c TC, #22-1pr TC, LSZH Jacket, Cca	Indoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only
1505ANH	1505ANH - 75 Ohm SDI Coax, RG-59, 20 AWG Solid BC, Foil + 95% TC Braid, LSZH-C Jkt	Indoor/Outdoor - Euroclass Dca	Indoor/Outdoor - Euroclass Dca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only
1505ELW	1505ELW - 75 Ohm SDI Coax, RG-59, 20 AWG Solid BC, Foil + 95% TC Braid, LSZH Jkt, CPR: Cca	Indoor/Outdoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only
1508ENH	AUDIO ANALOG 1 PAIR, 24AWG, ISTP, LSZH	Indoor	Indoor/Outdoor - Euroclass Eca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only
1510ELW	AUDIO ANALOG 4 PAIR 24AWG, BELDFOIL, LSZH-C	Indoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only
1512ENH	AUDIO ANALOG 8 PAIR 24AWG, BELDFOIL, LSZH	Indoor	Indoor/Outdoor - Euroclass Eca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only
1513ELW	AUDIO ANALOG 12 PAIR 24AWG, BELDFOIL, LSZH-C	Indoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only
1694ANH	1694ANH - 75 Ohm SDI Coax, RG-6, 18 AWG, Solid BC, Foil + 95% TC Braid, LSZH-C Jkt	Indoor/Outdoor - Euroclass Dca	Indoor/Outdoor - Euroclass Dca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only
1694ELV	1694ELV - 75 Ohm SDI Coax, RG-6, 18 AWG, Solid BC, Foil + 95%	Indoor/Outdoor - Euroclass B2ca	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non-Halogenated, Sunlight

	TC Braid, LSZH Jkt, CPR: B2ca		Resistance - UL 1581 sec 1200 Black only
1694ELW	1694ELW - 75 Ohm SDI Coax, RG-6, 18 AWG, Solid BC, Foil + 95% TC Braid, LSZH Jkt, CPR: Cca	Indoor/Outdoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only
1855ELW	1855ELW - 75 Ohm SDI Coax, Mini RG-59, 22 AWG Solid BC, Foil + 90% TC Braid, LSZH Jkt, CPR: Cca	Indoor/Outdoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only
1855ENH	1855ENH - 75 Ohm SDI Coax, Mini RG-59, 22 AWG Solid BC, Foil + 90% TC Braid, LSZH Jkt	Indoor/Outdoor - Euroclass Dca	Indoor/Outdoor - Euroclass Dca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only
3076ENH	Profibus PA, 1PR #18 Str TC, PO ins, OS, LSNH Jkt, 300 V	Indoor - Euroclass Eca, Sunlight Resistance	Indoor/Outdoor - Euroclass Eca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only
3076ENH	Profibus PA, 1PR #18 Str TC, PO ins, OS, LSNH Jkt, 300 V	Indoor - Euroclass Eca, Sunlight Resistance	Indoor/Outdoor - Euroclass Eca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only
3077ENH	Fieldbus, 1PR #22 Str TC, PO ins, OS, LSNH Jkt, 300 V	Indoor	Indoor/Outdoor, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only
3077ENH	Fieldbus, 1PR #22 Str TC, PO ins, OS, LSNH Jkt, 300 V	Indoor - Euroclass Eca	Indoor/Outdoor - Euroclass Eca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only
3079ANH	Profibus DP, 1PR #22 Sol BC, PO ins, F/B, LSNH Jkt, 300 V	Indoor - Euroclass Eca	Indoor/Outdoor - Euroclass Eca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only
3079ANH	Profibus DP, 1PR #22 Sol BC, PO ins, F/B, LSNH Jkt, 300 V	Indoor - Euroclass Eca	Indoor/Outdoor - Euroclass Eca, Indoor, Outdoor, Non- Halogenated, Sunlight

EMEA HEADQUARTERS

Belden Wire & Cable b.v. - Edisonstraat 9 - 5928 PG Venlo - The Netherlands
P: +31 77 387 8555

			Resistance - UL 1581 sec 1200 Black only
3105ELW	RS-485, 1 Pr #22 Str TC, FoamPE ins, F/B, LSZH Jkt, Cca	Indoor - Euroclass Cca, Indoor, Non- Halogenated, Sunlight Resistance, Oil Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
3106ELW	RS-485, 1.5Pr #22 Str TC, FoamPE ins, F/B, LSZH Jkt, Cca	Indoor - Euroclass Cca, Indoor, Non- Halogenated, Sunlight Resistance, Oil Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
3107ELV	RS-485, 2 Pr #22 Str TC, FoamPE ins, F/B, LSZH Jkt, B2ca	Indoor - Euroclass B2ca, Indoor, Non- Halogenated, Sunlight Resistance, Oil Resistance	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
3107ELW	RS-485, 2 Pr #22 Str TC, FoamPE ins, F/B, LSZH Jkt, Cca	Indoor - Euroclass Cca, Indoor, Non- Halogenated, Sunlight Resistance, Oil Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4000ULW	Security & Sound, 4 Conductor 12 AWG BC, LSZH, Cca	Indoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4002ULW	Security & Sound, 4 Conductor 12 AWG BC, LSZH, Cca	Indoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4100FLW	Security & Sound, 2 Conductor 14 AWG BC, LSZH, Shielded, Cca	Indoor - Euroclass Cca, Indoor, Non-Halogenated	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4100ULV	Security & Sound, 2 Conductor 14 AWG BC, LSZH, B2ca	Indoor - Euroclass B2ca, Indoor, Non-Halogenated	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4100ULW	Security & Sound, 2 Conductor 14 AWG BC, LSZH, Cca	Indoor - Euroclass Cca, Indoor, Non-Halogenated	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight

EMEA HEADQUARTERS

Belden Wire & Cable b.v. - Edisonstraat 9 - 5928 PG Venlo - The Netherlands
P: +31 77 387 8555

			Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4102ULV	Security & Sound, 4 Conductor 14 AWG BC, LSZH	Indoor - Euroclass B2ca	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4102ULW	Security & Sound, 4 Conductor 14 AWG BC, LSZH	Indoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4200FLW	Security & Sound, 2 Conductor 16 AWG BC, LSZH, Shielded, Cca	Indoor - Euroclass Cca, Non-Halogenated	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4200ULV	Security & Sound, 2 Conductor 16 AWG BC, LSZH, B2ca	Indoor - Euroclass Cca	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4200ULW	Security & Sound, 2 Conductor 16 AWG BC, LSZH, Cca	Indoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4202ULW	Security & Sound, 4 Conductor 16 AWG BC, LSZH, Cca	Indoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4300FLV	Security & Sound, 2 Conductor 18 AWG BC, LSZH, Shielded, B2ca	Indoor - Euroclass B2ca, Indoor, Non-Halogenated	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4300FLW	Security & Sound, 2 Conductor 18 AWG BC, LSZH, Shielded, Cca	Indoor - Euroclass Cca, Indoor, Non-Halogenated	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4300ULV	Security & Sound, 2 Conductor 18 AWG BC, LSZH, B2ca	Indoor - Euroclass Cca, Indoor, Non-Halogenated	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non- Halogenated, Sunlight

EMEA HEADQUARTERS

Belden Wire & Cable b.v. - Edisonstraat 9 - 5928 PG Venlo - The Netherlands
P: +31 77 387 8555

			Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4300ULW	Security & Sound, 2 Conductor 18 AWG BC, LSZH, Cca	Indoor - Euroclass Cca, Indoor, Non-Halogenated	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4301FLW	Security & Sound, 3 Conductor 18 AWG BC, LSZH, Shielded, Cca	Indoor - Euroclass Cca, Indoor, Non-Halogenated	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4301ULW	Security & Sound, 3 Conductor 18 AWG BC, LSZH, Cca	Indoor - Euroclass Cca, Indoor, Non-Halogenated	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4302FLW	Security & Sound, 4 Conductor 18 AWG BC, LSZH, Shielded, Cca	Indoor - Euroclass Cca, Indoor, Non-Halogenated	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4302ULV	Security & Sound, 4 Conductor 18 AWG, BC, LSZH, B2ca	Indoor - Euroclass Cca, Indoor, Non-Halogenated	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4302ULW	Security & Sound, 4 Conductor 18 AWG BC, BC, LSZH, Cca	Indoor - Euroclass Cca, Indoor, Non-Halogenated	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4303FLW	Security & Sound, 5 Conductor 18 AWG BC twisted cable, LSZH, Shielded, Cca	Indoor - Euroclass Cca, Indoor, Non-Halogenated	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4304FLV	Security & Sound, 6 Conductor 18 AWG, BC, LSZH, Shielded, B2ca	Indoor - Euroclass Cca, Indoor, Non-Halogenated	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4304FLW	Security & Sound, 6 Conductor 18 AWG	Indoor - Euroclass Cca, Indoor, Non-Halogenated	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight

EMEA HEADQUARTERS

Belden Wire & Cable b.v. - Edisonstraat 9 - 5928 PG Venlo - The Netherlands
P: +31 77 387 8555

	BC, BC, LSZH, Shielded, Cca		Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4304ULW	Security & Sound, 6 Conductor 18 AWG BC, LSZH, Cca	Indoor - Euroclass Cca, Indoor, Non-Halogenated	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4305ULW	Security & Sound, 7 Conductor 18 AWG BC, LSZH, Cca	Indoor - Euroclass Cca, Indoor, Non-Halogenated	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4306FLW	Security & Sound, 8 Conductor 18 AWG BC, LSZH, Shielded, Cca	Indoor - Euroclass Cca, Indoor, Non-Halogenated	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4309FLW	Security & Sound, 12 Conductor 18 AWG, BC, shielded, LSZH, Cca	Indoor - Euroclass Cca, Indoor, Non-Halogenated	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4309ULW	Security & Sound, 12 Conductor 18 AWG BC, LSZH, Cca	Indoor - Euroclass Cca, Indoor, Non-Halogenated	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
430BULW	Security & Sound, 20 Conductor 18 AWG BC, LSZH, Cca	Indoor - Euroclass Cca, Indoor, Non-Halogenated	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4340FDW	OSDP RS485, 1PR #18 Str TC, PO ins, OS, LSNH Jkt, Cca	Indoor - Euroclass Cca, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4341FDW	OSDP RS485, 2PR #18 Str TC, PO ins, OS, LSNH Jkt, Cca	Indoor - Euroclass Cca, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4341FLV	Security & Sound, 2 Pair 18 AWG BC, LSZH, Shielded, B2ca	Indoor - Euroclass B2ca	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non- Halogenated, Sunlight

EMEA HEADQUARTERS

Belden Wire & Cable b.v. - Edisonstraat 9 - 5928 PG Venlo - The Netherlands
P: +31 77 387 8555

			Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4341FLW	Security & Sound, 2 Pair 18 AWG BC, LSZH, Shielded, Cca	Indoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4342FDW	OSDP RS485, 3 Pr #18 Str TC, PO Ins, OS, LSZH Jkt, Cca	Indoor - Euroclass Cca, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4342ULW	Security & Sound, 3 Pairs 18 AWG BC, LSZH, Cca	Indoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4343FDW	OSDP RS485, 4 Pr #18 Str TC, PO Ins, OS, LSZH Jkt, Cca	Indoor - Euroclass Cca, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4343FLV	Security & Sound, 4 Pair 18 AWG BC, LSZH, Shielded, B2ca	Indoor - Euroclass B2ca	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4343FLW	Security & Sound, 4 Pair 18 AWG BC, LSZH, Shielded, Cca	Indoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4348ULV	Security & Sound, 12 Pairs 18 AWG BC, LSZH, B2ca	Indoor - Euroclass B2ca	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4381MDV	1Pr 24AWG Shielded Data + 18/2 Power OSDP, B2ca	Indoor - Euroclass B2ca, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4381MDW	1Pr 24AWG Shielded Data + 18/2 Power OSDP, Cca	Indoor - Euroclass Cca, Indoor, Non-	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight

EMEA HEADQUARTERS

Belden Wire & Cable b.v. - Edisonstraat 9 - 5928 PG Venlo - The Netherlands
P: +31 77 387 8555

		Halogenated, Sunlight Resistance	Resistance - UL 1581 sec 1200 Black only, Oil Resistance
43906LW	LIGHTNING CONTROL DMX512 LSZH	Indoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4400ULW	Security & Sound, 2 Conductor 20 AWG BC, LSZH, Cca	Indoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4401FLW	Security & Sound, 3 Conductor 20 AWG BC, LSZH, Cca	Indoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4402FLW	Security & Sound, 4 Conductor 20 AWG BC, LSZH, Shielded, Cca	Indoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4440FDW	OSDP RS485, 1PR #20 Str TC, PO ins, OS, LSNH Jkt, Cca	Indoor - Euroclass Cca, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4441FDW	OSDP RS485, 2PR #20 Str TC, PO ins, OS, LSNH Jkt, Cca	Indoor - Euroclass Cca, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4441FLV	Security & Sound, 2 Pair 20AWG BC, LSZH, Shielded, B2ca	Indoor - Euroclass B2ca	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4441FLW	Security & Sound, #20-2pr, BC, LSZH, Shielded, Cca	Indoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4442FDW	OSDP RS485, 3 Pr #20 Str TC, PO Ins, OS, LSZH Jkt, Cca	Indoor - Euroclass Cca, Indoor, Non-	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight

EMEA HEADQUARTERS

Belden Wire & Cable b.v. - Edisonstraat 9 - 5928 PG Venlo - The Netherlands
P: +31 77 387 8555

		Halogenated, Sunlight Resistance	Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4442FLV	Security & Sound, 3 Pair 20 AWG, BC, LSZH, Shielded, B2ca	Indoor - Euroclass B2ca	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4442FLW	Security & Sound, 3 Pair 20 AWG, BC, LSZH, Shielded, Cca	Indoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4443FDW	OSDP RS485, 4 Pr #20 Str TC, PO Ins, OS, LSZH Jkt, Cca	Indoor - Euroclass Cca, Indoor, Non-Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4500FLV	Security & Sound, 2 Conductor 22 AWG BC, LSZH, Shielded, B2ca	Indoor - Euroclass B2ca	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4500FLW	Security & Sound, 2 Conductor 22 AWG BC, LSZH, Shielded, Cca	Indoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4501FLW	Security & Sound, 3 Conductor 22 AWG BC, BC, LSZH, Shielded, Cca	Indoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4502FLV	Security & Sound, 4 Conductor 22 AWG BC, BC, LSZH, Shielded, B2ca	Indoor - Euroclass B2ca	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4502FLW	Security & Sound, 4 Conductor 22 AWG BC, BC, LSZH, Shielded, Cca	Indoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4502ULW	Security & Sound, 4 Conductor 22 AWG BC, BC, LSZH, Cca	Indoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight

EMEA HEADQUARTERS

Belden Wire & Cable b.v. - Edisonstraat 9 - 5928 PG Venlo - The Netherlands
P: +31 77 387 8555

			Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4504FLV	Security & Sound, 6 Conductor 22 AWG BC, BC, LSZH, Shielded, B2ca	Indoor - Euroclass B2ca	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4504FLW	Security & Sound, 6 Conductor 22 AWG BC, BC, LSZH, Shielded, Cca	Indoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4505ELW	4K UHD Coax for 12G- SDI, 75 Ohm, RG-59, 20 AWG Solid SC, Foil + 95% TC Braid, LSZH Jkt	Indoor - Euroclass Cca, Indoor, Non-Halogenated	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4506FLV	Security & Sound, 8 Conductor 22 AWG BC, LSZH, Shielded, B2ca	Indoor - Euroclass B2ca	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4506FLW	Security & Sound, 8 Conductor 22 AWG BC, LSZH, Shielded, Cca	Indoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4540FDW	OSDP RS485, 1PR #22 Str TC, PO ins, OS, LSNH Jkt, Cca	Indoor - Euroclass Cca, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4541FDV	OSDP RS485, 2PR #22 Str TC, PO ins, OS, LSNH Jkt, B2ca	Indoor - Euroclass B2ca, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4541FDW	OSDP RS485, 2PR #22 Str TC, PO ins, OS, LSNH Jkt, Cca	Indoor - Euroclass Cca, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4542FDW	OSDP RS485, 3 Pr #22 Str TC, PO Ins, OS, LSZH Jkt, Cca	Indoor - Euroclass Cca, Indoor, Non-	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight

EMEA HEADQUARTERS

Belden Wire & Cable b.v. - Edisonstraat 9 - 5928 PG Venlo - The Netherlands
P: +31 77 387 8555

		Halogenated, Sunlight Resistance	Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4542FLW	Security & Sound, 3 Pair 22 AWG, BC, LSZH, Shielded, Cca	Indoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4543FDW	OSDP RS485, 4 Pr #22 Str TC, PO Ins, OS, LSZH Jkt, Cca	Indoor - Euroclass Cca, Indoor, Non-Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4545FLW	Security & Sound, 6 Pair 22 AWG BC, LSZH, Shielded, Cca	Indoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4640FDW	OSDP RS485, 1 Pr #24 Str TC, PO Ins, OS, LSZH Jkt, Cca	Indoor - Euroclass Cca, Indoor, Non-Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4641FDW	OSDP RS485, 2 Pr #24 Str TC, PO Ins, OS, LSZH Jkt, Cca	Indoor - Euroclass Cca, Indoor, Non-Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4642FDW	OSDP RS485, 3 Pr #24 Str TC, PO Ins, OS, LSZH Jkt, Cca	Indoor - Euroclass Cca, Indoor, Non-Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4643FDW	OSDP RS485, 4 Pr #24 Str TC, PO Ins, OS, LSZH Jkt, Cca	Indoor - Euroclass Cca, Indoor, Non-Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4694ANH	12 GHz Coax, 4K UHD Precision Video Coax, RG-6/U Type, 75 Ohm, 18 AWG Solid, CMG-LS	Indoor - Euroclass Dca, Indoor, Aerial - Black only, When supported by messenger wire	Indoor/Outdoor - Euroclass Dca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4694ELW	4K UHD Coax for 12G-SDI, 75 Ohm, RG-6, 18 AWG Solid SC, Foil +	Indoor - Euroclass Cca, Indoor, Non-Halogenated	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight

EMEA HEADQUARTERS

Belden Wire & Cable b.v. - Edisonstraat 9 - 5928 PG Venlo - The Netherlands
P: +31 77 387 8555

	95% TC Braid, LSZH Jkt		Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4794ELW	4K UHD Coax for 12G-SDI, 75 Ohm, Series 7, 16 AWG Solid SC, Foil + 95% TC Braid, LSZH Jkt	Indoor - Euroclass Cca, Indoor, Non-Halogenated	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4I20ULV	Security & Sound, 2 Conductor 0.5mm ² BC, LSZH, B2ca	Indoor - Euroclass B2ca	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
4T01ULW	Security & Sound, 3 Conductor 10 AWG BC, LSZH, Cca	Indoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
558ALV	Access Control, 16c (#22-3pr, #18-4c, #22-4c, #22-2c), Shielded, LSZH Banana Peel®, CMG-LS	Indoor (Not Riser or Plenum), Indoor	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
558ALW	Access Control, 16c (#22-3pr, #18-4c, #22-4c, #22-2c), Shielded, LSZH Banana Peel®, CMG-LS	Indoor (Not Riser or Plenum), Indoor	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
70001NH	Profibus PA, 1PR #18 Str TC, PO ins, F/B, LSNH Jkt, 300 V	Indoor, Sunlight Resistance	Indoor/Outdoor - Euroclass Eca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
70001NH	Profibus PA, 1PR #18 Str TC, PO ins, F/B, LSNH Jkt, 300 V	Indoor, Sunlight Resistance	Indoor/Outdoor - Euroclass Eca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
70006NH	DataTuff® 5E, 1Q #22 Sol BC, PO ins, F/B, LSNH Jkt, PROFINET Type A, AWM 21286	Indoor - Euroclass Eca, Sunlight Resistance, Oil Resistance	Indoor/Outdoor - Euroclass Eca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200, Oil Resistance
70007NH	DataTuff® 5E, 1Q #22 Str TC, PO ins, F/B,	Indoor - Euroclass Eca, Sunlight Resistance, Oil Resistance	Indoor/Outdoor - Euroclass Eca, Indoor, Outdoor, Non-Halogenated, Sunlight

EMEA HEADQUARTERS

Belden Wire & Cable b.v. - Edisonstraat 9 - 5928 PG Venlo - The Netherlands
P: +31 77 387 8555

	LSNH Jkt, PROFINET Type B UL AWM 21286		Resistance - UL 1581 sec 1200, Oil Resistance
70045LV	Speaker Cable LSZH 2x1.5mm ² , CPR B2ca.	Indoor/Outdoor - Euroclass B2ca	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
70045LW	Speaker Cable LSZH 2x1.5mm ² , CPR Cca.	Indoor/Outdoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
70046LV	Speaker Cable LSZH 2x2.5mm ² , CPR B2ca.	Indoor/Outdoor - Euroclass B2ca	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
70046LW	Speaker Cable LSZH 2x2.5mm ² , CPR Cca.	Indoor/Outdoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
70047LV	Speaker Cable LSZH 4x2.5mm ² , CPR B2ca.	Indoor/Outdoor - Euroclass B2ca	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
70048LV	Speaker Cable LSZH 2x4.0mm ² , CPR B2ca.	Indoor/Outdoor - Euroclass B2ca	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
70049LV	1 PAIR AES/EBU, 24AWG, ISTP, LSZH-C	Indoor - Euroclass B2ca	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
70049LW	1 PAIR AES/EBU, 24AWG, ISTP, LSZH	Indoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
70050LW	1 PAIR AES/EBU, 22AWG, ISTP, LSZH-C	Indoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight

EMEA HEADQUARTERS

Belden Wire & Cable b.v. - Edisonstraat 9 - 5928 PG Venlo - The Netherlands
P: +31 77 387 8555

			Resistance - UL 1581 sec 1200 Black only, Oil Resistance
70057LV	2 PAIR AES/EBU, 24AWG, ISTP, LSZH	Indoor - Euroclass B2ca	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
70057LW	2 PAIR AES/EBU, 24AWG, ISTP, LSZH	Indoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
70058LW	4 PAIR AES/EBU, 24AWG, ISTP, LSZH	Indoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
70059LV	8 PAIR AES/EBU, 24AWG, ISTP, LSZH-C	Indoor - Euroclass B2ca	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
70059LW	8 PAIR AES/EBU, 24AWG, ISTP, LSZH-C	Indoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
70070LW	4 PAIR AES/EBU, 22AWG, ISTP, LSZH-C	Indoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
70071LW	8 PAIR AES/EBU, 22AWG, ISTP, LSZH-C	Indoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
70086LV	Speaker Cable LSZH 2x6.0mm ² , CPR B2ca.	Indoor/Outdoor - Euroclass B2ca	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
70086LW	Speaker Cable LSZH 2x6.0mm ² , CPR Cca.	Indoor/Outdoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight

EMEA HEADQUARTERS

Belden Wire & Cable b.v. - Edisonstraat 9 - 5928 PG Venlo - The Netherlands
P: +31 77 387 8555

			Resistance - UL 1581 sec 1200 Black only, Oil Resistance
70087LW	Media Control, #16-2c TC, #22-1pr TC, LSZH Jacket, CCa	Indoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
71730ELW	RS-485, 1 Pr #18Str TC, PO Ins, OS+TC Brd, LSZH Jkt, Cca	Indoor - Euroclass Eca, Indoor, Non-Halogenated, Sunlight Resistance, Oil Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
71731ELW	RS-485, 2 Pr #18 Str TC, PO Ins, OS+TC Brd, LSZH Jkt, Cca	Indoor - Euroclass Eca, Indoor, Non-Halogenated, Sunlight Resistance, Oil Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
71732ELW	RS485, 3 Pr #18 Str TC, PE Ins, OS+TC Brd, LSZH Jkt, Cca	Indoor - Euroclass Eca, Indoor, Non-Halogenated, Sunlight Resistance, Oil Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
71733ELW	RS485, 4 Pr #18 Str TC, PE Ins, OS+TC Brd, LSZH Jkt, Cca	Indoor - Euroclass Eca, Indoor, Non-Halogenated, Sunlight Resistance, Oil Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
71740ELW	RS-485, 1 Pr #20 Str TC, PO Ins, OS+TC Brd, LSZH Jkt, Cca	Indoor - Euroclass Eca, Indoor, Non-Halogenated, Sunlight Resistance, Oil Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
71741ELW	RS-485, 2 Pr #20 Str TC, PO Ins, OS+TC Brd, LSZH Jkt, Cca	Indoor - Euroclass Eca, Indoor, Non-Halogenated, Sunlight Resistance, Oil Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
71742ELW	RS485, 3 Pr #20 Str TC, PE Ins, OS+TC Brd, LSZH Jkt, Cca	Indoor - Euroclass Eca, Indoor, Non-Halogenated, Sunlight Resistance, Oil Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
71743ELW	RS485, 4 Pr #20 Str TC, PE Ins, OS+TC Brd, LSZH Jkt, Cca	Indoor - Euroclass Eca, Indoor, Non-Halogenated, Sunlight	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight

		Resistance, Oil Resistance	Resistance - UL 1581 sec 1200 Black only, Oil Resistance
72001ELW	DataTuff® 5E, 2PR #24 Sol BC, PO ins, SF/UTP, LSNH Jkt, Cca	Indoor, Sunlight Resistance, Oil Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
72001NH	DataTuff® 5E, 2PR #24 Sol BC, PO ins, SF/UTP, LSNH Jkt, AWM 21286	Indoor, Sunlight Resistance, Oil Resistance	Indoor/Outdoor - Euroclass Eca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200, Oil Resistance
72002NH	DataTuff® 5E, 2PR #26 Str BC, PO ins, SF/UTP, LSNH Jkt, AWM 21286	Indoor - Euroclass Eca, Sunlight Resistance, Oil Resistance	Indoor/Outdoor - Euroclass Eca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200, Oil Resistance
74001NH	DataTuff® 5E, 4PR #24 Sol BC, PO ins, SF/UTP, LSNH Jkt, AWM 21286	Indoor - Euroclass Eca, Sunlight Resistance, Oil Resistance	Indoor/Outdoor - Euroclass Eca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200, Oil Resistance
74002NH	DataTuff® 5E, 4PR #26 Str BC, PO ins, SF/UTP, LSNH Jkt, AWM 21286	Indoor - Euroclass Eca, Sunlight Resistance, Oil Resistance	Indoor/Outdoor - Euroclass Eca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200, Oil Resistance
74004ELV	DataTuff® 7, 4PR #23 Sol BC, PO ins, S/FTP, LSNH Jkt, AWM 20851, B2ca	Indoor - Euroclass B2ca, Indoor, Sunlight Resistance - Black only, Oil Resistance	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
74004ELW	DataTuff® 7, 4PR #23 Sol BC, PO ins, S/FTP, LSNH Jkt, AWM 20851, Cca	Indoor - Euroclass Cca, Indoor, Sunlight Resistance - Black only, Oil Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
74004NH	DataTuff® 7, 4PR #23 Sol BC, PO ins, S/FTP, LSNH Jkt, AWM 20851, Dca	Indoor - Euroclass Dca, Sunlight Resistance, Oil Resistance	Indoor/Outdoor - Euroclass Dca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200, Oil Resistance
74005NH	DataTuff® 7, 4PR #26 Str BC, PO ins, S/FTP, LSNH Jkt, AWM 20851	Indoor - Euroclass Dca, Sunlight Resistance, Oil Resistance	Indoor/Outdoor - Euroclass Dca, Indoor, Outdoor, Non- Halogenated, Sunlight

			Resistance - UL 1581 sec 1200, Oil Resistance
74010NH	DataTuff® 6A, 4PR #22 Sol BC, PO ins, S/FTP, LSNH Jkt, PROFINET Type A, AWM 20851	Indoor - Euroclass Eca, Sunlight Resistance, Oil Resistance	Indoor/Outdoor - Euroclass Eca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200, Oil Resistance
74011NH	DataTuff® 6A, 4PR #23 Str BC, PO ins, S/FTP, LSNH Jkt, PROFINET Type B, AWM 20851	Indoor - Euroclass Eca, Sunlight Resistance, Oil Resistance	Indoor/Outdoor - Euroclass Eca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200, Oil Resistance
7701ELW	LonWorks, 1PR #22 Sol BC, PO ins, Unsh, LSNH Jkt, 300V, Cca	Indoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
7704ELV	LonWorks, 2PR #22 Sol BC, PO ins, OS, LSNH Jkt, 300V, B2ca	Indoor - Euroclass B2ca	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
7704ELW	LonWorks, 2PR #22 Sol BC, PO ins, OS, LSNH Jkt, 300V, Cca	Indoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
7731ANH	7731ANH - 75 Ohm SDI Coax, RG-11, 14 AWG Solid BC, Foil + 95% TC Braid, LSZH-C Jkt	Indoor/Outdoor - Euroclass Dca	Indoor/Outdoor - Euroclass Dca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
7731ELW	7731ELW - 75 Ohm SDI Coax, RG-11, 14 AWG Solid BC, Foil + 95% TC Braid, LSZH Jkt; CPR: Cca	Indoor/Outdoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
7784ANH	7784ANH - Triax 11, 15 AWG Solid SPC, Double BC Braids, LSZH-C Jkt	Indoor/Outdoor - Euroclass Eca	Indoor/Outdoor - Euroclass Eca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
7784ELW	7784ELW - Triax 11, 15 AWG Solid BC, Double BC Braids, LSZH-C Jkt	Indoor/Outdoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight

EMEA HEADQUARTERS

Belden Wire & Cable b.v. - Edisonstraat 9 - 5928 PG Venlo - The Netherlands
P: +31 77 387 8555

			Resistance - UL 1581 sec 1200 Black only, Oil Resistance
7785ANH	7785ANH - Triax 14, 11 AWG Str SPC, SPC + BC Braids, LSZH-C Jkt	Indoor	Indoor/Outdoor - Euroclass Eca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
77905ELV	KNX, 1PR 0.8mm Sol BC, LSZH ins, OS, LSZH Jkt, B2ca	Indoor - Euroclass B2ca	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
77905ELW	KNX, 1PR 0.8mm Sol BC, LSZH ins, OS, LSZH Jkt, Cca	Indoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
77906ELV	KNX, 2PR 0.8mm Sol BC, LSZH ins, OS, LSZH Jkt, B2ca	Indoor - Euroclass B2ca	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
77906ELW	KNX, 2PR 0.8mm Sol BC, LSZH ins, OS, LSZH Jkt, Cca	Indoor - Euroclass Cca	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
7804ELV	Indoor/Mobile Duty SMPTE 311M Cable, 2 Fiber, 2 Conductor 24 AWG, 4 Conductor 20 AWG, FRNC jacket	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Sunlight Resistance - Black only	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
7804ELW	Indoor/Mobile Duty SMPTE 311M Cable, 2 Fiber, 2 Conductor 24 AWG, 4 Conductor 20 AWG, FRNC jacket	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Sunlight Resistance - Black only	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
7810ELW	RF400 Wireless Coax, RG8, 10 AWG	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Aerial - Black only, When supported by messenger wire	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
7824ELW	3-Channel SMPTE Stadium Cable, 6 Fiber, 6 Conductor 18	Indoor - Euroclass Cca, Indoor	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight

EMEA HEADQUARTERS

Belden Wire & Cable b.v. - Edisonstraat 9 - 5928 PG Venlo - The Netherlands
P: +31 77 387 8555

	AWG, 6 Conductor 24 AWG, FRNC, Cca		Resistance - UL 1581 sec 1200 Black only, Oil Resistance
8102NH	RS232/422 Low Cap, #24-2pr, FPO, O/A Foil+Braid, LSZH Jkt, Dca, 100Ω	Indoor - Euroclass Dca	Indoor/Outdoor - Euroclass Dca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
8110NH	RS232/422 Low Cap, #24-10pr, FPO, O/A Foil+Braid, LSZH Jkt, Dca, 100Ω	Indoor	Indoor/Outdoor, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
8205ELW	Electronic, 1PR #20 Str TC, FRNC ins, Unsh, LSNH Jkt, 300V, Cca	Indoor - Euroclass Cca, Indoor, Non-Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
8205NH	Electronic, 1PR #20 Str TC, LSZH ins, Unsh, LSNH Jkt, 300V, Dca	Indoor - Euroclass Dca, Sunlight Resistance	Indoor/Outdoor - Euroclass Dca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
8305ELW	RS-232, Low Cap, #22-5pr, LSZH, O/A Foil+Braid, LSZH Jkt,Cca	Indoor - Euroclass Cca, Indoor	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
8471ELV	Electronic, 2 C #16 Str TC, LSZH Ins, LSZH Jkt, B2ca	Indoor - Euroclass B2ca, Indoor, Non-Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
8471ELW	Electronic, 2 C #16 Str TC, LSZH Ins, LSZH Jkt, Cca	Indoor - Euroclass Cca, Indoor, Non-Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
8471NH	Electronic, 2 C #16 Str TC, LSZH Ins, LSZH Jkt	Indoor - Euroclass Dca, Indoor, Non-Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Dca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
8719ELV	Electronic, 2 C #16 Str TC, PE Ins, OS, LSZH Jkt, B2ca	Indoor - Euroclass B2ca, Indoor, Non-Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non-Halogenated, Sunlight

EMEA HEADQUARTERS

Belden Wire & Cable b.v. - Edisonstraat 9 - 5928 PG Venlo - The Netherlands
P: +31 77 387 8555

			Resistance - UL 1581 sec 1200 Black only, Oil Resistance
8719ELW	Electronic, 2 C #16 Str TC, PE Ins, OS, LSZH Jkt, Cca	Indoor - Euroclass Cca, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
8719NH	Electronic, 2 C #16 Str TC, PE Ins, OS, LSZH Jkt, Dca	Indoor - Euroclass Dca, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Dca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
8723LV	Audio, Control & Instrument, #22-2pr, PO, Individ. Foil, LSZH Jkt, B2ca	Indoor - Euroclass B2ca, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
8723LW	Audio, Control & Instrument, #22-2pr, PO, Individ. Foil, LSZH Jkt, Cca	Indoor - Euroclass Cca, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
8723NH	Audio, Control & Instrument, #22-2pr, PO, Individ. Foil, LSZH Jkt, Dca	Indoor - Euroclass Dca, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Dca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
8760ELV	Electronic, 2 C #18 Str TC, PE Ins, OS, LSZH Jkt, B2ca	Indoor - Euroclass B2ca, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
8760ELW	Electronic, 2 C #18 Str TC, PE Ins, OS, LSZH Jkt, Cca	Indoor - Euroclass Cca, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
8760NH	Electronic, 2 C #18 Str TC, PE Ins, OS, LSZH Jkt, Dca	Indoor - Euroclass Dca, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Dca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
8761ELV	Electronic, 2 C #22 Str TC, PE ins, OS, LSZH Jkt, B2ca	Indoor - Euroclass B2ca, Indoor, Non-	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non- Halogenated, Sunlight

		Halogenated, Sunlight Resistance	Resistance - UL 1581 sec 1200 Black only, Oil Resistance
8761ELW	Electronic, 2 C #22 Str TC, PE ins, OS, LSZH Jkt, Cca	Indoor - Euroclass Cca, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
8761NH	Electronic, 2 C #22 Str TC, PE ins, OS, LSZH Jkt, Dca	Indoor - Euroclass Dca, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Dca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
8762ELV	Electronic, 2 C #20 Str TC, PE ins, OS, LSZH Jkt, B2ca	Indoor - Euroclass B2ca, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
8762ELW	Electronic, 2 C #20 Str TC, PE ins, OS, LSZH Jkt, Cca	Indoor - Euroclass Cca, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
8762NH	Electronic, 2 C #20 Str TC, PE ins, OS, LSZH Jkt, Dca	Indoor - Euroclass Dca, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Dca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
8770ELW	Electronic, 3C #18 Str TC, PO ins, OS, LSNH Jkt 300V, Cca	Indoor - Euroclass Cca, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
8770NH	Electronic, 3C #18 Str TC, PO ins, OS, LSNH Jkt 300V	Indoor, Non-Halogenated	Indoor/Outdoor - Euroclass Dca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
8771NH	Electronic, 3C #22 Str TC, PO ins, OS, LSNH Jkt 300V	Indoor - Euroclass Eca, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Eca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
8772ELV	Electronic, 3C #20 Str TC, PO ins, OS, LSNH Jkt 300V, B2ca	Indoor - Euroclass B2ca, Indoor, Non-Halogenated	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non- Halogenated, Sunlight

EMEA HEADQUARTERS

Belden Wire & Cable b.v. - Edisonstraat 9 - 5928 PG Venlo - The Netherlands
P: +31 77 387 8555

			Resistance - UL 1581 sec 1200 Black only, Oil Resistance
8772ELW	Electronic, 3C #20 Str TC, PO ins, OS, LSNH Jkt 300V, Cca	Indoor - Euroclass Cca, Indoor, Non-Halogenated	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
8772NH	Electronic, 3C #20 Str TC, PO ins, OS, LSNH Jkt 300V	Indoor - Euroclass Dca, Indoor, Non-Halogenated	Indoor/Outdoor - Euroclass Dca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
8777ELV	Audio, Control & Instrument, #22-3pr, PP, Individ. Foil, LSZH Jkt, B2ca	Indoor - Euroclass B2ca, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
8777ELW	Audio, Control & Instrument, #22-3pr, PP, Individ. Foil, LSZH Jkt, Cca	Indoor - Euroclass Cca, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
8777NH	Audio, Control & Instrument, #22-3pr, PP, Individ. Foil, LSZH Jkt	Indoor - Euroclass Dca, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Dca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
8778ELW	Audio, Control & Instrument, #22-6pr, LSZH, Individ. Foil, LSZH Jkt, Cca	Indoor - Euroclass Cca, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
8778NH	Audio, Control & Instrument, #22-6pr, PP, Individ. Foil, LSZH Jkt, Dca	Indoor - Euroclass Dca, Sunlight Resistance	Indoor/Outdoor - Euroclass Dca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
9182NH	Twinax , 1PR #22 Str TC, PO ins, OS, LSNH Jkt, 300V	Indoor - Euroclass Eca, Sunlight Resistance	Indoor/Outdoor - Euroclass Eca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
9182NH	Twinax , 1PR #22 Str TC, PO ins, OS, LSNH Jkt, 300V	Indoor - Euroclass Eca, Sunlight Resistance	Indoor/Outdoor - Euroclass Eca, Indoor, Outdoor, Non- Halogenated, Sunlight

EMEA HEADQUARTERS

Belden Wire & Cable b.v. - Edisonstraat 9 - 5928 PG Venlo - The Netherlands
P: +31 77 387 8555

			Resistance - UL 1581 sec 1200 Black only, Oil Resistance
9207NH	100Ω Twinax, 1 Pr #20 Str-1c TC/1c BC, PE Jkt, Duofoil®+TC Braid, LSZH Jkt, IEC-60332- 3C	Indoor - Euroclass Eca	Indoor/Outdoor - Euroclass Eca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
9463NH	Blue Hose, 1PR #20 Str TC, PO ins, F/B, LSNH Jkt,	Indoor - Euroclass Eca, Sunlight Resistance	Indoor/Outdoor - Euroclass Eca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
9463NH	Blue Hose, 1PR #20 Str TC, PO ins, F/B, LSNH Jkt,	Indoor - Euroclass Eca, Sunlight Resistance	Indoor/Outdoor - Euroclass Eca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
9501NH	RS-232, 1PR #24 Str TC, PO ins, OS, LSZH Jkt, 300V, Dca	Indoor - Euroclass Dca, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Dca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
9502ELW	RS-232, 2PR #24 Str TC, LSZH ins, OS, LSZH Jkt, 300 V,Cca	Indoor - Euroclass Cca, Sunlight Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
9502NH	RS-232, 2PR #24 Str TC, PO ins, OS, LSZH Jkt, 300 V	Indoor - Euroclass Dca, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Dca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
9503ELW	RS-232, 3PR #24 Str TC, PO ins, OS, LSZH Jkt, 300V, Cca	Indoor - Euroclass Cca, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
9503NH	RS-232, 3PR #24 Str TC, PO ins, OS, LSZH Jkt, 300V	Indoor - Euroclass Dca, Sunlight Resistance	Indoor/Outdoor - Euroclass Dca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
9504ELW	RS-232, 4PR #24 Str TC, LSZH ins, OS, LSZH Jkt, 300V, Cca	Indoor - Euroclass Cca, Sunlight Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight

			Resistance - UL 1581 sec 1200 Black only, Oil Resistance
9504NH	RS-232, 4PR #24 Str TC, PO ins, OS, LSZH Jkt, 300V, Dca	Indoor - Euroclass Dca, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Dca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
9505NH	RS-232, 5PR #24 Str TC, PO ins, OS, LSZH Jkt, 300V, Dca	Indoor - Euroclass Dca, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Dca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
9506ELW	RS-232, 6PR #24 Str TC, LSZH ins, OS, LSZH Jkt, 300V, Cca	Indoor - Euroclass Cca, Sunlight Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
9506NH	RS-232, 6PR #24 Str TC, PO ins, OS, LSZH Jkt, 300V, Dca	Indoor - Euroclass Dca, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Dca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
9507NH	RS-232, 7PR #24 Str TC, PO ins, OS, LSZH Jkt, 300V, Dca	Indoor - Euroclass Dca, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Dca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
9508NH	RS-232, 8PR #24 Str TC, PO ins, OS, LSZH Jkt, 300V, Dca	Indoor - Euroclass Dca, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Dca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
9510NH	RS-232, 10PR #24 Str TC, PO ins, OS, LSZH Jkt, 300V	Indoor, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Eca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
9534NH	RS-232, 4C #24 Str TC, PO ins, OS, LSZH Jkt, 300V, Dca	Indoor - Euroclass Dca, Sunlight Resistance	Indoor/Outdoor - Euroclass Dca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
9535ELW	RS-232, 5C #24 str TC, LSZH ins, OS, LSZH Jkt, Cca	Indoor - Euroclass Cca, Sunlight Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight

EMEA HEADQUARTERS

Belden Wire & Cable b.v. - Edisonstraat 9 - 5928 PG Venlo - The Netherlands
P: +31 77 387 8555

			Resistance - UL 1581 sec 1200 Black only, Oil Resistance
9536ELV	RS-232, 6C #24 Str TC, PO ins, OS, LSZH Jkt, 300V, B2ca	Indoor - Euroclass B2ca, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
9536ELW	RS-232, 6C #24 Str TC, PO ins, OS, LSZH Jkt, 300V, Cca	Indoor - Euroclass Cca, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
9536NH	RS-232, 6C #24 Str TC, PO ins, OS, LSZH Jkt, 300V	Indoor - Euroclass Dca, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Dca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
9538ELW	RS232, #24-8c, FRNC/LSZH, O/A Foil, FRNC/LSZH Jkt, Cca	Indoor - Euroclass Cca, Indoor	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
9538NH	RS-232, 8C #24 Str TC, PO ins, OS, LSZH Jkt, 300V	Indoor/Outdoor - Euroclass Dca, Indoor, Non-Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Dca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
9541NH	RS-232, 15C #24 Str TC, PO ins, OS, LSZH Jkt, 300V, Dca	Indoor - Euroclass Dca	Indoor/Outdoor - Euroclass Dca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
9542ELW	RS232, #24-20c, FRNC/LSZH, O/A Foil, FRNC/LSZH Jkt, Cca	Indoor - Euroclass Cca, Indoor	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
9729ELW	RS232/422 Low Cap, #24-2pr, FPO, Indiv. Foil, LSZH Jkt, 100Ω, Cca	Indoor - Euroclass Cca, Indoor, Non- Halogenated, Sunlight Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
9729NH	RS232/422 Low Cap, #24-2pr, FPO, Indiv. Foil, LSZH Jkt, 100Ω	Indoor - Euroclass Dca, Indoor, Non-	Indoor/Outdoor - Euroclass Dca, Indoor, Outdoor, Non- Halogenated, Sunlight

EMEA HEADQUARTERS

Belden Wire & Cable b.v. - Edisonstraat 9 - 5928 PG Venlo - The Netherlands
P: +31 77 387 8555

		Halogenated, Sunlight Resistance	Resistance - UL 1581 sec 1200 Black only, Oil Resistance
9773ELW	Audio, Control & Instrument, #18-3pr, LSZH Ins, Individ. Foil, LSZH Jkt, Cca	Indoor	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
9829NH	RS232/422 Low Cap, #24-2pr, PE, O/A Foil+Braid, LSZH Jkt, Dca, 100Ω	Indoor - Euroclass Dca, Sunlight Resistance	Indoor/Outdoor - Euroclass Dca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
9841LV	RS-485, 1 Pr #24 Str TC, PE Ins, OS+TC Brd, LSZH Jkt, B2ca	Indoor - Euroclass B2ca, Indoor, Non-Halogenated, Sunlight Resistance, Oil Resistance	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
9841LW	RS-485, 1 Pr #24 Str TC, PE Ins, OS+TC Brd, LSZH Jkt, Cca	Indoor - Euroclass Cca, Indoor, Non-Halogenated, Sunlight Resistance, Oil Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
9841NH	RS-485, 1 Pr #24 Str TC, PE Ins, OS+TC Brd, LSZH Jkt, Dca	Indoor - Euroclass Dca, Indoor, Non-Halogenated, Sunlight Resistance, Oil Resistance	Indoor/Outdoor - Euroclass Dca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
9842LV	RS-485, 2 Pr #24 Str TC, PE Ins, OS+TC Brd, LSZH Jkt, B2ca	Indoor - Euroclass B2ca, Indoor, Non-Halogenated, Sunlight Resistance, Oil Resistance	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
9842LW	RS-485, 2 Pr #24 Str TC, PE Ins, OS+TC Brd, LSZH Jkt, Cca	Indoor - Euroclass Cca, Indoor, Non-Halogenated, Sunlight Resistance, Oil Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
9842NH	RS-485, 2 Pr #24 Str TC, PE Ins, OS+TC Brd, LSZH Jkt, Dca	Indoor - Euroclass Dca, Indoor, Non-Halogenated, Sunlight Resistance, Oil Resistance	Indoor/Outdoor - Euroclass Dca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
9843NH	RS-485, 3 Pr #24 Str TC, PE Ins, OS+TC Brd, LSZH Jkt, Dca	Indoor - Euroclass Dca, Indoor, Non-Halogenated, Sunlight	Indoor/Outdoor - Euroclass Dca, Indoor, Outdoor, Non-Halogenated, Sunlight

		Resistance, Oil Resistance	Resistance - UL 1581 sec 1200 Black only, Oil Resistance
9844LW	RS-485, 4 Pr #24 Str TC, PE Ins, OS+TC Brd, LSZH Jkt, Cca	Indoor - Euroclass Cca, Indoor, Non- Halogenated, Sunlight Resistance, Oil Resistance	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
9844NH	RS-485, 4 Pr #24 Str TC, PE Ins, OS+TC Brd, LSZH Jkt, Eca	Indoor - Euroclass Eca, Indoor, Non- Halogenated, Sunlight Resistance, Oil Resistance	Indoor/Outdoor - Euroclass Eca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only, Oil Resistance
9925ELW	RS232/423 Low Cap, #24-3c, FPO, O/A Foil+Braid,LSZH Jkt, Cca	Indoor, Indoor	Indoor/Outdoor - Euroclass Cca, Indoor, Outdoor, Non- Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black only

EMEA HEADQUARTERS

Belden Wire & Cable b.v. - Edisonstraat 9 - 5928 PG Venlo - The Netherlands
P: +31 77 387 8555