



Product: [H125A00](#)

COAX H125 AL PVC CATV

Product Description
COAX [1.0/4.8] H125 AL PVC CATV

Technical Specifications

Product Overview

Suitable Applications:	Coaxial cables used in cabled distribution networks designed according the European Standard EN 50117-2-1 and EN 50117-2-4; Operating at frequencies between 5 MHz and 3000 MHz
------------------------	---

Physical Characteristics (Overall)

Conductor					
AWG	Stranding	Material	Nominal Diameter	Diameter +/- Tolerance	No. of Coax
18	Solid	BC - Bare Copper	1 mm	0.03 mm	1
Conductor Count:			1		

Insulation			
Type	Material	Nominal Diameter	Diameter +/- Tolerance
Dielectric	PE - Polyethylene (Foam)	4.8 mm	0.15 mm

Outer Shield Material						
Type	Layer	Material	Coverage [%]	Min. Overlap	Nominal Diameter	Coverage +/- Tolerance
Tape	1	Tri-Laminate (Alum+Poly+Alum)	34%	1 mm		
Braid	2	Tinned Copper (TC)	34%		5.4 mm	4%

Outer Jacket Material		
Material	Nominal Diameter	Diameter +/- Tolerance
PVC - Polyvinyl Chloride	6.8 mm	0.2 mm

Table Notes:	According to European Standard EN 50290-2-20
--------------	--

Construction and Dimensions

Min Elongation at Breakof Jacket:	150 %
Min Tensile Strength of Jacket:	12.5 MPa

Electrical Characteristics

Conductor DCR		
Max. Conductor DCR	Max. Conductor Loop	Max. Shield DCR
23 Ohm/km	50 Ohm/1000ft	27 Ohm/km

Capacitance	
Nom. Capacitance	Capacitance Tolerance
55 pF/m	2 pF/m

Impedance		
Nominal Characteristic Impedance	Nominal Characteristic Tolerance	Regularity of Impedance
75 Ohm	3 Ohm	Min. 40 dB

High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
5 MHz	1.8 dB/100m
50 MHz	4.7 dB/100m
100 MHz	6.5 dB/100m
200 MHz	9.1 dB/100m
230 MHz	9.8 dB/100m
400 MHz	12.9 dB/100m
600 MHz	16 dB/100m
800 MHz	18.6 dB/100m
862 MHz	19.3 dB/100m
1000 MHz	20.9 dB/100m
1350 MHz	24.6 dB/100m
1750 MHz	28.4 dB/100m
2400 MHz	34 dB/100m
3000 MHz	38.6 dB/100m

Table Notes:	Max. attenuation 10% higher
--------------	-----------------------------

Delay

Nominal Velocity of Propagation (VP) [%]	Velocity of Propagation Tolerance
81%	2%

High Freq

Frequency [MHz]	Min. RL (Return Loss) [dB]
5 - 30 MHz	23 dB
30 - 470 MHz	23 dB
470 - 1000 MHz	20 dB
1000 - 2000 MHz	18 dB
2000 - 3000 MHz	16 dB

Table Notes:	In each frequency band, 3 peak values up to 4 dB lower are allowed
--------------	--

Screening

Frequency [MHz]	Min. Screening Attenuation
100 - 1000 MHz	75 dB

Screening Class:	B
------------------	---

Transfer Impedance

Transfer Impedance
40 mOhm/m

Transfer Impedance Class:	C
---------------------------	---

Voltage

Element	Non-UL Voltage Rating	Voltage Test Dielectric
		2.0 kV DC
Voltage test jacket	3750 DC V	

Temperature Range

Installation Temp Range:	-5°C To +50°C
Storage Temp Range:	-40°C To +70°C
Operating Temp Range:	-40°C To +70°C

Mechanical Characteristics

Min Bend Radius (W/o Pulling Strength):	35 mm
Crush Resistance:	Max. 1% (load of 700N) N
Adhesion Dielectric:	No shrinkback N

Standards

CPR Euroclass:	Eca
CENELEC Compliance:	EN 50117-2-1, EN 50117-2-4 and EN 50117-1
RG Type:	6/U Type

Applicable Environmental and Other Programs

Environmental Space:	Indoor - Euroclass Eca
EU RoHS Compliance Date (yyyy-mm-dd):	1998-01-01

Flammability, LSOH, Toxicity Testing

IEC Flammability:	IEC 60332-1-2
-------------------	---------------

Part Number

Variants

Item #	Color	Putup Type	Length	EAN
H125A00.01100	Black	Reel	100 m	8719605086341
H125A00.01B100	Black	Flat Box	100 m	8719605086372
H125A00.01U250	Black	UnReel	250 m	8719605086389
H125A00.01500	Black	Reel	500 m	8719605086358
H125A00.015000	Black	Reel	5,000 m	8719605086365
H125A00.02B100	Brown	Flat Box	100 m	8719605086396
H125A00.00100	White	Reel	100 m	8719605086242
H125A00.00B100	White	Flat Box	100 m	8719605086310
H125A00.00U150	White	UnReel	150 m	8719605086327
H125A00.00200	White	Reel	200 m	8719605086266
H125A00.00250	White	Reel	250 m	8719605086273
H125A00.00U250	White	UnReel	250 m	8719605086334
H125A00.00500	White	Reel	500 m	8719605086280
H125A00.001000	White	Reel	1,000 m	8719605086259
H125A00.005000	White	Reel	5,000 m	8719605086297
H125A00.105000	White	Reel	5,000 m	8719605086433

History

Update and Revision:	Revision Number: 0.173 Revision Date: 09-30-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.