



Part Number: 74002PU

DataTuff® Industrial Ethernet Cat 5e Moderate Flexing Cable



Product Description

DataTuff Industrial ETHERNET, CAT 5E 4P, 1 Gb/s, AWG 26(7), Stranded, Foil + 80% Braid, No Halogen Jacket PUR, UL AWM 20549

Technical Specifications

Product Overview

Environmental Space:	Indoor
----------------------	--------

Physical Characteristics (Overall)

Conductor				
AWG	Stranding	Material	Construction n x D	No. of Pairs
26	Stranded	BC - Bare Copper	7x0.16 mm	4
Conductor Count:				8
Total Number of Pairs:				4
Conductor Size:				26 AWG

Insulation		
Material	Nominal Diameter	Diameter +/- Tolerance
PP - Polypropylene	0.98 mm	0.05 mm

Color Chart	
Number	Color
Pair 1	White/Blue & Blue
Pair 2	White/Orange & Orange
Pair 3	White/Green & Green
Pair 4	White/Brown & Brown

Outer Shield Material		
Type	Material	Min. Coverage [%]
Tape	Aluminum/Polyester	
Braid	TC - Tinned Copper	80 %

Note:	Aluminum outside
-------	------------------

Outer Jacket Material				
Material	Color	Nominal Diameter	Diameter +/- Tolerance	
PUR (Halogenfree and flame-retardant)	Black	6.5 mm	0.2 mm	

Construction and Dimensions

Min Elongation at Breakof Conductors:	10 %
Min Elongation at Breakof Insulation:	100 %
Min Elongation at Breakof Jacket:	100 %
Min Tensile Strength of Jacket:	15 MPa

Electrical Characteristics

Conductor DCR	
Max. Conductor DCR	Max. DCR Unbalanced Within Pair [%]

145 Ohm/km	2 Ohm
------------	-------

Capacitance

Max. Capacitance Unbalance	Max. Mutual Capacitance
1.6 pF/m	56 pF/m

Shielding:	SF/UTP - Overall Braid + Foil
------------	-------------------------------

Impedance

Nominal Characteristic Impedance	Nominal Characteristic Tolerance	Nominal Input Impedance
100 Ohm	5 Ohm	100 +/- 15 Ohm

Delay

Max. Delay Skew	Nominal Velocity of Propagation (VP) [%]
40 ns/100m	60 %

High Freq

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Min. NEXT [dB]	Min. PSNEXT [dB]	Min. ACRF (ELFEXT) [dB]	Min. PSACRF (PSELFEXT) [dB]	Min. RL (Return Loss) [dB]
0.772 MHz		67 dB	64 dB			19.4 dB
1 MHz	3.2 dB/100m	65.3 dB	62.3 dB	63.8 dB	60.8 dB	20 dB
4 MHz	6 dB/100m	56.3 dB	53.3 dB	51.8 dB	48.8 dB	23 dB
10 MHz	9.5 dB/100m	50.3 dB	47.3 dB	43.8 dB	40.8 dB	25 dB
16 MHz	12.1 dB/100m	47.2 dB	44.2 dB	39.7 dB	36.7 dB	25 dB
20 MHz	13.6 dB/100m	45.8 dB	42.8 dB	37.8 dB	34.8 dB	25 dB
25 MHz	15.3 dB/100m	44.3 dB	41.3 dB	35.8 dB	32.8 dB	24.3 dB
31.25 MHz	17.1 dB/100m	42.9 dB	39.9 dB	33.9 dB	40.9 dB	23.6 dB
62.5 MHz	24.8 dB/100m	38.3 dB	35.4 dB	27.9 dB	24.9 dB	21.5 dB
100 MHz	32 dB/100m	35.3 dB	32.3 dB	23.8 dB	20.8 dB	20.1 dB

Current

Element	Max. Recommended Current [A]
Conductor	1 A

Voltage

Voltage Rating [V]
450 V DC and 300 V AC

Temperature Range

Installation Temp Range:	-15°C To +60°C
Storage Temp Range:	-40°C To +80°C
Operating Temp Range:	-40°C To +80°C

Mechanical Characteristics

Oil Resistance:	IEC 60811-2-1
Max Recommended Pulling Tension:	80 N
Min Bend Radius (W/o Pulling Strength):	70 mm
Min Setting Radius:	35 mm

Standards

UL AWM Style:	UL AWM 20549
ISO/IEC Compliance:	ISO/IEC 11801 Ed. 2.2:2002/A2:2010/C1:2011 and ISO/IEC 24702
CENELEC Compliance:	EN 50173-1 Ed. 3:2011
Data Category:	Category 5e
ANSI Compliance:	ANSI/TIA/EIA 568-B.2-1 (2002)

Applicable Environmental and Other Programs

EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
---------------------------------------	------------

Flammability, LS0H, Toxicity Testing

CSA Flammability:	FT2
Amount of Halogen acc. to IEC 60754-1 & EN50267-1:	Zero

Part Number

Variants

Item #	Color
74002PU.011000	Black
74002PU.01305	Black
74002PU.01500	Black

Patent:	https://www.belden.com/resources/patents
---------	---

History

Revision Number:	1
------------------	---

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.