# **Product Datasheet**

#### **Armoured Patch Cords**

Armoured patch cords are used in customer premises, central offices and in harsh environments. The patch cords provide flexible interconnection to active equipment, passive optical devices and cross-connects. Armoured patch cords are constructed with an helical stainless steel tape over a buffered fibre surrounded by a layer of aramid and stainless steel mesh with an outer jacket.

Our patch cords are terminated with our standard range of connectors, all quality tested to meet our and international standards.



Further images available on request

#### **Features**

- SC, LC, ST and FC connectors
- Available in low smoke zero halogen (LSZH) jacket
- Conforms to IEC, EIA-TIA or Telcordia performance requirements
- Available in different fibre types
- Available in standard and custom lengths
- REACH, SvHC and RoHS materials compliant

### **Applications**

- CATV / VIDEO
- Passive Optical Network PON
- FTTX
- ATM, SONET and WDM
- Military applications

### **Specification**

### **Connector Specification**

OPTICAL PERFORMANCE	SINGLEMODE	MULTIMODE	CONFORMANCE
IL Max/Master (Acceptance)	0.25dB	0.25dB	IEC 61300-3-4
Ave/Master	0.18dB	0.2dB	IEC 61300-3-4
Ave/Random	0.18dB	-	IEC 61300-3-34
Return Loss Singlemode UPC/APC	55/65 dB	-	IEC 61300-3-6

## **Fibre Specification**

#### **CHARACTERISTICS**

 $\begin{array}{lll} \text{Attenuation (dB/km) Singlemode} & 0.38@1310\text{nm} \ / \ 0.25 \ @1550\text{nm} \\ \text{Chromatic Dispersion (ps/nm x km) Singlemode} & 3.0 \ @ \ 1310\text{nm} \ / \ 18.0 \ @1550\text{nm} \\ \text{Attenuation (dB/km) Multimode} & 2.8@850\text{nm} \ / \ 0.8 \ @1300\text{nm} \\ \end{array}$ 

#### **Cable Specification**

CHARACTERISTICS	SIMPLEX	DUPLEX
Cable Material	LSZH	LSZH
Strength Member	Aramid	Aramid
Crush (N) short term	3000	3000
Crush (N) long term	200	200
Operating Temperature (°C)	-20 to 60	-20 to 60
Fire Specification	IEC 60332-1	IEC 60332-1

#### **Ordering Information**

Connector End A		Connector End B		
FC	FC	FC	FC	
FCA	FC APC	FCA	FC APC	
SC	SC	SC	SC	
SCA	SC APC	SCA	SC APC	
ST	ST	ST	ST	
LC	LC	LC	LC	

1	Mode		
	09	OS1/OS2	
	62	OM1	
	50	OM2	
	ОМЗ	OM3	
	ОМ4	OM4	
1			

	Cable Configuration		
]	S	Simplex 3mm	
	D	Duplex 3.3mm	

	Cable Colour		
BL	SM Blue		
GY	OM1/OM2 Grey		
ΑQ	OM3/OM4 Aqua		

Cable Length			
1	1 metre		
2	2 meter	ľ	
3	3 meter		
5	5 meter		
10	10 meter		
хx	Specify		




#### **Example Part Number**

FC SC OM4 S AQ 3 /ARM

This part number has created a 3 metre simplex FC to SC OM4 armoured patch cord in aqua.

## **Technical Drawing**



#### **Further Information**

Information correct as of November 30, 2015