

Datasheet

SPEAKERCABLE Eca

Acc. to EN 50575:2014

GRADE A, 99,9% pure Oxygen Free Copper

STANDARD	2 x 0,75 mm ²	2 x 1,50mm ²	2 x 2,50mm ²
Core	24 x 0,20 mm	48 x 0,20 mm	78 x 0,20 mm
Insolation	PVC, Black with red stripe or Transparant with red stripe	PVC, Black with red stripe or Transparant with red stripe	PVC, Black with red stripe or Transparant with red stripe
Dimensions (+/- 0,15 mm)	2,2 mm x 4,8 mm	2,6 mm x 5,8 mm	3,60 mm x 7,5 mm
Wall thickness (+/- 0,10 mm)	0,57 mm	0,63 mm	0,58 mm
Weight (gr/mtr)	23,0	37,0	62,0
Copper weight (gr/mtr)	14,4	30,0	50
Conductor Res. Ohm/km	22,00 per conductor	11,00 per conductor	6,83 per conductor

STANDARD	2 x 4,00 mm ²	2 x 6,00mm ²
Core	126 x 0,20 mm	189 x 0,20 mm
Insolation	PVC Transparant with red stripe	PVC, Transparant with red stripe
Dimensions (+/- 0,15 mm)	4,4 mm x 9,5 mm	5,2 mm x 10,8 mm
Wall thickness (+/- 0,10 mm)	0,90 mm	0,90 mm
Weight (gr/mtr)	105	141
Copper weight (gr/mtr)	80	120
Conductor Res. Ohm/km	4,20 per conductor	3,30 per conductor

-Made in Germany-

