

PRODUCT INFORMATION

ULTIMEG 2000/T4 XYLENE MIXED ISOMERS

ULTIMEG 2000/T4 THINNERS **GENERAL DESCRIPTION**

Ultimeg UT4 thinners is a hydrocarbon solvent based on xylene with mixed isomers. The material is an extremely good cutting agent for the majority of the Ultimeg 2000 range of varnishes. It can also be used as a general purpose cleaning solvent that offers excellent degreasing and cleaning properties.

SPECIFICATION

Colour	clear
Density at 15°C	0.868
Initial Boiling Point °C	138.0
50% Distils at °C	139.1
Dry Boiling Point °C	141.0
Flash Point °C	25
Aromatic Content % v/v	99.5
Benzene Content % v/v	NND
N-Hexane Content % w/w	NND
Aniline Point °C	9.5
Kauri Butanol Value	94
Viscosity at 20°C (cSt)	0.76
Refractive Index at 20°C	1.495
Vapour Pressure at 20°C calc.m.bar	7.0
Lower Explosive Limit % v/v	1.0
Upper Explosive Limit % v/v	6.5
Autoignition Temperature °C	490
Surface Tension at 20°C mN/m	30.5
Litres/Tonne at 15°C	1152
Conforms To	BS 458/2

Issue No. 1 rc 02/02

NOTE: Due to the introduction of improvements from time to time the right is reserved to supply products that may differ slightly from those illustrated or described in this publication.

Email: aev@aev.co.uk
www.aev.co.uk

AEV PLC,
Marion Street, Birkenhead,
Wirral. U.K CH41 6LT
Tel: ++ 44 (0) 151 647 3322
Fax: ++ 44 (0) 151 647 3377