

**Product:** [74001E](#) 

DataTuff® 5E, 4PR #24 Sol BC, PO ins, SF/UTP, PVC jkt, AWM 2464



## Product Description

DataTuff® 5E, 4 Pair AWG 24 Bare Copper - Solid, Polyolefin (PO, PE, PP) insulation, SF/UTP - Overall Braid + Foil shielding, PVC jacket , AWM 2464

## Technical Specifications

### Physical Characteristics (Overall)

#### Conductor

AWG	Stranding	Material	No. of Pairs
24	Solid	BC - Bare Copper	4

Conductor Count:	8
Total Number of Pairs:	4

#### Insulation

Material	Nominal Diameter	Diameter +/- Tolerance
Polyolefin	1.1 mm	0.05 mm

Bonded-Pair:	No
--------------	----

#### Color Chart

Number	Color
Pair 1	White/Blue & Blue
Pair 2	White/Orange & Orange
Pair 3	White/Green & Green
Pair 4	White/Brown & Brown

#### Outer Shield Material

Type	Material	Min. Coverage [%]
Tape	Alum / Poly	
Braid	TC - Tinned Copper	80 %

Outer Shield Table Note:	Aluminum outside
--------------------------	------------------

#### Outer Jacket Material

Material	Nominal Diameter	Diameter +/- Tolerance	Min. Wall Thickness	Nominal Wall Thickness
PVC - Polyvinyl Chloride	6.8 mm	0.3 mm	0.8 mm	0.8 mm

### Construction and Dimensions

Min Elongation at Breakof Conductors:	10 %
Min Elongation at Breakof Insulation:	100 %
Min Elongation at Breakof Jacket:	100 %
Min Tensile Strength of Jacket:	15 MPa

### Electrical Characteristics

#### Conductor DCR

Max. Conductor DCR	Max. Conductor Loop	Max. DCR Unbalanced Within Pair [%]
--------------------	---------------------	-------------------------------------

93.8 Ohm/km	19 Ohm/1000ft	2 %
-------------	---------------	-----

#### Capacitance

Max. Capacitance Unbalance	Max. Mutual Capacitance
1.6 pF/m	56 pF/m

#### Impedance

Nominal Characteristic Impedance	Nominal Characteristic Tolerance	Nominal Input Impedance
100 Ohm	5 Ohm	100 +/- 15 Ohm

#### Delay

Max. Delay Skew	Nominal Velocity of Propagation (VP) [%]
40 ns/100m	60 %

#### Current

Element	Max. Recommended Current [A]
Conductor	1.4 A

#### Voltage

Voltage Rating [V]
450 V DC and 300 V AC

### Temperature Range

Installation Temp Range:	-15°C To +60°C
Operating Temp Range:	-40°C To +80°C

### Mechanical Characteristics

Oil Resistance:	IEC 60811-2-1
Max Recommended Pulling Tension:	80 N
Min Bend Radius (W/o Pulling Strength):	54 mm
Min Setting Radius:	27 mm

### Standards

ISO/IEC Compliance:	ISO/IEC 11801 Ed. 2.2:2002/A2:2010/C1:2011 and ISO/IEC 24702
CPR Euroclass:	Eca
CENELEC Compliance:	EN 50173-1 Ed. 3:2011
Data Category:	Category 5e
ANSI Compliance:	ANSI/TIA 568.2-D (2018)
IEEE Specification:	PoE: IEEE 802.3bt Type 1, Type 2, Type 3

### Applicable Environmental and Other Programs

Environmental Space:	Indoor - Euroclass Eca
EU RoHS Compliance Date (yyyy-mm-dd):	2016-01-08

### Suitability

Suitability - Oil Resistance:	Yes
Suitability - Sunlight Resistance:	Yes - Black only

### Flammability, LSOH, Toxicity Testing

ISO/IEC Flammability:	IEC 60332-1-2
-----------------------	---------------

### Part Number

#### Variants

Item #	Color	Putup Type	Length	EAN
74001E.012000	Black	Reel	2,000 m	8719605012937
74001E.01305	Black	Reel	305 m	8719605012944
74001E.01B100	Black	Flat Box	100 m	8719605012968
74001E.01500	Black	Reel	500 m	8719605012951

Patent:	<a href="https://www.belden.com/resources/patents">https://www.belden.com/resources/patents</a>
---------	---

### History

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.